



Universal Octo-LNB

Digital LNB with 8 legacy outputs

| EAN | Colour | Item no. | Weight (Box) | Weight | Device (W x H x D) | Box |
|---------------|--------|-----------|--------------|--------|----------------------|--------------------|
| 4019588083981 | black | 0000/8398 | 302 g | 266 g | 5,7 x 10,9 x 13,4 cm | 11,5 x 14 x 6,4 cm |

TOP FEATURES

For 8 participant

Feed ø 40 mm

F connectors

LTE interference-safe

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 2,5 MHz

Phase noise : -83 @10kHz

FILTER-NAVIGATION

Number satellites : 1

Number participants : 8

LNB CONTROL

Vertical : 11,5 ... 14,5 V

Horizontal : 16 ... 19 V

Band switch : 22 kHz

AMBIENT OPERATING CONDITIONS

Ambient temperature : -40 ... 70 °C

Humidity : 10 ... 95 %

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : typ. 1 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

POWER SUPPLY

Power consumption : 210 mA

PREPARED FOR

Number of orbit positions : 1

Number of clients : 8

TECHNICAL DATA

Impedance : 75 Ω

Feed reception : 40 mm

Outputs : 8

Connector type : F female

Amplification : 58 ... 65 dB

SCOPE OF DELIVERY

Universal-Octo-LNB