



Universal-Quattro-Switch-LNB

Digital LNB with 4 legacy outputs

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
black	4019588083905	0000/8390	234 g	200 g	5,7 x 10,1 x 12,8 cm	10,2 x 13,8 x 6,1 cm

TOP FEATURES

For 4 participant

Feed ø 40 mm

F connectors

LTE interference-safe

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 2,5 MHz

Phase noise : -85 @10kHz

FILTER-NAVIGATION

Number satellites : 1

Number participants : 4

LNB CONTROL

Vertical : 10,5 ... 14,5 V

Horizontal : 16 ... 22 V

Band switch : 22 kHz

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 95 %

Ambient temperature : -40 ... 70 °C

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : typ. 0,75 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

POWER SUPPLY

Power consumption : typ. 150 mA

PREPARED FOR

Number of orbit positions : 1

Number of clients : 4

TECHNICAL DATA

Impedance : 75 Ω

Feed reception : 40 mm

Connector type : F female

Outputs : 4

Amplification : 60 ... 65 dB

SCOPE OF DELIVERY

Universal-Quattro-Switch-LNB