



In addition to the statutory warranty, you receive a 20-year warranty for this product – no product registration required. All information about warranty conditions

SATMAN 65 PLUS with UNYSAT-Quattro-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 65 cm Ø

Colour	EAN	Item no.	Weight (Box)	Weight
beige	4019588888005	2065/8880	6,6 kg	4,2 kg
slate/grey	4019588888036	2365/8880	6,6 kg	4,2 kg
brick/red	4019588888043	2465/8880	6,6 kg	4,2 kg
polar/white	4019588888074	2765/8880	6,6 kg	4,2 kg
yellow with Smiley	4019588888050	2565/8880	6,6 kg	4,2 kg

TOP FEATURES

65 cm Spiegel aus erstklassigem Aluminium (beidseitig pulverbeschichtet)

Ausgelegt für viele Teilnehmer, Verteilung erfolgt durch Multischalter oder TECHNIROUTER

1 Orbitposition (z. B. Astra 19,2° Ost)

Optimal für Wand- und Dachmontage

LNB mit Wetterschutzgehäuse

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,7 GHz

LNB CONTROL

Vertical : 11,5 - 14,5 V

Horizontal : 16 - 19 V

GENERAL CHARACTERISTICS

Material : Aluminium

Material strength : 1,5 mm

Coating : Powder-coated on both sites

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Lower frequency range : 0,6 dB max.

Upper frequency range : 0,6 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

TECHNICAL DATA

F/D : 0,69

G/T : 14,5

Offset angle : 27 °

Gain : 35,7 dBi @11,3 GHz

Mast Ø : 65 mm max.

Feed reception : for UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish antenna SATMAN 65, AZ/EL bracket mount, UNSYSAT-Quattro-LNB, screws, installation instructions