



8 way satellite splitter

for the 8-fold distribution of Sat signals

Colour	EAN	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
silver	4019588223103	0022/3110	136 g	130 g	11,8 x 6 x 1,7 cm	14,5 x 10 x 1,7 cm

TOP FEATURES

DC power pass

DiSEqC-compatible

diode decoupled

TECHNIROUTER-compatible

DECOUPLING

5 - 862 MHz : Typ. 22 dB

950 - 1750 MHz : Typ. 22 dB

1750 - 2150 MHz : Typ. 21 dB

950 - 1750 MHz : Typ. 15 dB (± 1)

1750 - 2150 MHz : Typ. 18 dB (± 1)

GENERAL CHARACTERISTICS

Top features : DC power pass

Top features : diode decoupled

Top features : DiSEqC-compatible

Top features : TECHNIROUTER-compatible

RETURN LOSS

5 - 862 MHz : Typ. 9 dB

950 - 1750 MHz : Typ. 13 dB

1750 - 2150 MHz : Typ. 11 dB

TECHNICAL DATA

Input : 1

Outputs : 8

Frequency range : 5 ... 2.150 MHz

Shielding factor : ≥ 75 dB EN 50083-2 (Class A)

Connector type : F female

Impedance : 75 Ω

TRANSMISSION LOSS

5 - 862 MHz : Typ. 12 dB (± 1)