



**2 YEARS WARRANTY**

**MADE IN GERMANY**

## TECHNISELECT 12

For feeding 12 selectable satellite transponders into a single cable distribution system

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032996	blue/yellow	0000/3299	800 g	500 g	29,2 x 11,2 x 3,1 cm	31,8 x 20 x 4,5 cm

### TOP FEATURES

Einspeisung von digitalen Sat-Signalen in vorhandene Kabelstrukturen

Eingang zum Empfang von Terrestrischen Signalen

4 vollwertige Receiverausgänge oder Sat-Stämme

Messausgang -20 dB

Stromsparfunktion

### LNB CONTROL

Vertical : 13 V über VL

Current consumption : max. 400 mA (für LNB und / oder Verstärker)

### AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %

Ambient temperature : -25 ... 55 °C

### DECOUPLING

Trunks : 30 dB

### GENERAL CHARACTERISTICS

Top features : Einspeisung von digitalen Sat-Signalen in vorhandene Kabelstrukturen

Top features : Eingang zum Empfang von Terrestrischen Signalen

Top features : 4 vollwertige Receiverausgänge oder Sat-Stämme

Top features : Messausgang -20 dB

Top features : Stromsparfunktion

### POWER CONSUMPTION

In operation : 11 W (inkl. LNB)

### POWER SUPPLY

Frequency : 50 Hz

Nominal voltage : 230 V

Mains adapter : internal

### RECEPTION RANGE

Sat : 950 ... 2.150 MHz

Terrestrial : 80 ... 790 MHz

### SINGLE-CABLE OUTPUT

Output frequency : 80 ... 2.150 MHz

Number of output channels : 12

Frequency of the output channels : 974, 1076, 1178, 1280, 1382, 1484, 1586, 1688, 1790, 1892, 1994, 2096 MHz

Frequency SAT : 950 ... 2.150 MHz

Frequency DVB-T : 80 ... 790 MHz

Output level : max. 105

Output level : 12 ... 20 dB (Einstellbare Verstärkung)

### TECHNICAL DATA

Satellite inputs : 4

Terrestrial input : 1

Number of cable connections : 1

Subscribers per cable : über 50

### TRANSMISSION LOSS

Terrestrial : -20 ... -12 dB (Einstellbare Verstärkung)

### SCOPE OF DELIVERY

TechniSelect 12, manual, CD-ROM with TechniSelect Configuration Tool, USB-cable



